

The complexity of

$$\mathfrak{A} \models \phi$$

FOL

SOL

\exists *SOL*

HornSOL

1

Computing $\mathcal{M}(\mathfrak{A}, z, \phi)$, I

Given

\mathfrak{A} , a τ -structure with $|A| = m$

$\phi \in FOL(\tau)$ of length n
and quantifier depth q

z an assignment $z : Var_{FOL} \rightarrow A$

We want to compute **inductively** the meaning function

$$\mathcal{M}(\mathfrak{A}, z, \phi)$$

and estimate its computational complexity with respect to time and space denoted by

$$TIME(\mathfrak{A}, z, \phi), SPACE(\mathfrak{A}, z, \phi)$$

2

CS 236 331:2001

Lecture 6

Computing $\mathcal{M}(\mathfrak{A}, z, \phi)$, II

Recall that τ is purely relational and terms t are either constants or variables.

Atomic formulas:

$R(t_1, t_2, \dots, t_r)$ with $R \in \tau$ and $t_1 \approx t_2$.

Takes one step in a random access look-up table.

Takes m^r , resp. m^2 steps for searching the table.

One bit space for the result.

Boolean operations:

$$\phi = (\phi_1 \wedge \phi_2), \phi = (\phi_1 \vee \phi_2), \phi = \neg \phi_1$$

$$TIME(\mathfrak{A}, z, \phi) = TIME(\mathfrak{A}, z, \phi_1) + TIME(\mathfrak{A}, z, \phi_2) + 1$$

$$SPACE(\mathfrak{A}, z, \phi) = \max(SPACE(\mathfrak{A}, z, \phi_1), SPACE(\mathfrak{A}, z, \phi_2))$$

3

CS 236 331:2001

Lecture 6

Computing $\mathcal{M}(\mathfrak{A}, z, \phi)$, III

Quantifiers:

$$\phi = \exists x \phi_1(x), \phi = \forall x \phi_1(x)$$

We search the structure for an element, hence
 $TIME(\mathfrak{A}, z, \phi) = m \cdot TIME(\mathfrak{A}, z, \phi_1)$

We can denote location of search in binary, hence

$$SPACE(\mathfrak{A}, z, \phi) = \log m \cdot SPACE(\mathfrak{A}, z, \phi_1)$$

Conclusion:

$$TIME(\mathfrak{A}, z, \phi) = O(n \cdot m^q)$$

$$SPACE(\mathfrak{A}, z, \phi) = O(q \cdot \log m)$$

4

Computing $\mathcal{M}(\mathfrak{A}, z, \phi)$, IV

We have considered two problems for *FOL*:

1. The combined complexity of $\mathcal{M}(\mathfrak{A}, z, \phi)$ where both \mathfrak{A} and ϕ are the input.

This is in *PSPACE*.

2. The complexity of $\mathcal{M}(\mathfrak{A}, z, \phi)$ for fixed ϕ , where only \mathfrak{A} is the input.

This is in **P** and even in *LOGSPACE* \subseteq **P**.

5

Computing $\mathcal{M}(\mathfrak{A}, z, \phi)$, V

Now we consider *SOL*.

The only change comes from the quantifiers: Search is over all subsets of A^r .

This takes time 2^{m^r} .

The characteristic function of these sets has size m^r .

Conclusion:

$$TIME(\mathfrak{A}, z, \phi) = O(n \cdot 2^{q \cdot m^r})$$

$$SPACE(\mathfrak{A}, z, \phi) = O(q \cdot \log m^r) = O(q \cdot r \cdot m)$$

6

Computing $\mathcal{M}(\mathfrak{A}, z, \phi)$, VI

We consider two problems for *SOL*:

1. The combined complexity of $\mathcal{M}(\mathfrak{A}, z, \phi)$ where both \mathfrak{A} and ϕ are the input.

This is also in *PSPACE*.

2. The complexity of $\mathcal{M}(\mathfrak{A}, z, \phi)$ for fixed ϕ , where only \mathfrak{A} is the input.

This is in *PSPACE*.

7

Computing $\mathcal{M}(\mathfrak{A}, z, \phi)$, VII

We want to use now non-deterministic machines.

We denote by $\exists SOL(\tau)$ the set of *SOL*(τ)-formulas ψ of the form

$$\psi = \exists X_1 \exists X_2 \dots \exists X_k \phi(X_1, X_2, \dots, X_k)$$

with $\phi \in FOL(\tau \cup \{X_1, X_2, \dots, X_k\})$

For fixed $\psi \in \exists SOL$ we have that $\mathcal{M}(\mathfrak{A}, z, \psi)$ is in **NP**.

Hence, for fixed $\psi \in SOL$ we have that $\mathcal{M}(\mathfrak{A}, z, \psi)$ is in **PH**, the **Polynomial Hierarchy**.

8

The Polynomial Hierarchy, I

We look at **Oracle Turing Machines** OTM .
Let X be a problem and C be a class of problems.

We define

$P^X = \{Y : \exists M \text{ accepts } Y \text{ using } X \text{ as oracle} \}$
 $P^C = \{Y : \exists M \text{ accepts } Y \text{ using } X \in C \text{ as oracle} \}$
 Here M is a deterministic polynomial time OTM .

Similarly,

$NP^X = \{Y : \exists M \text{ accepts } Y \text{ using } X \text{ as oracle} \}$
 $NP^C = \{Y : \exists M \text{ accepts } Y \text{ using } X \in C \text{ as oracle} \}$
 Here M is a non-deterministic polynomial time OTM .

9

The Polynomial Hierarchy, II

We define inductively:

$$\Delta_0 P = \Sigma_0 P = \Pi_0 P = P$$

and

$$\begin{aligned}\Delta_{i+1} P &= P^{\Sigma_i P} \\ \Sigma_{i+1} P &= NP^{\Sigma_i P} \\ \Pi_{i+1} P &= \text{CoNP}^{\Sigma_i P}\end{aligned}$$

Finally,

$$PH = \bigcup_{i \in \mathbb{N}} \Sigma_i P$$

Note that $PH \subseteq PSPACE$ and
 $P = NP$ iff $P = PH$.

10

CS 236 331:2001

Lecture 6

Horn formulas, I

A **propositional Horn clause** is a formula of the form

$$\neg p_1 \vee \neg p_2 \vee \dots \vee \neg p_m \vee q$$

with at most one variable unnegated.

Equivalently, we can write

$$(p_1 \wedge p_2 \wedge \dots \wedge p_m \rightarrow q)$$

$m = 0$ gives $\text{true} \rightarrow q$ and the absence of q gives

$$(p_1 \wedge p_2 \wedge \dots \wedge p_m \rightarrow \text{false})$$

or

$$\neg(p_1 \wedge p_2 \wedge \dots \wedge p_m)$$

A *FOL* Horn clause is obtained by replacing variables by atomic formulas.

11

CS 236 331:2001

Lecture 6

Horn formulas, II

The **size** $s(C)$ of a **clause** C is the number of variables occurring in Σ .

The **size** $s(\Sigma)$ of **set of clauses** Σ is defined as $\sum_{C \in \Sigma} s(C)$

SAT is the problem of deciding whether a set Σ of clauses with n variables of size m is satisfiable.

Theorem: *SAT* can be solved in $TIME(2^n \cdot m)$ and is **NP**-complete.

HORN SAT is like *SAT* but with Σ a set of Horn clauses.

Theorem: *HORN SAT* is in **P**.

Proof: Use unit resolution.

12

Horn formulas, III

The formulas of *Horn* \exists *SOL* are of the form

$$\Psi = \exists X_1 \exists X_2 \dots \exists X_j \forall x_1 \forall x_2 \dots \forall x_k \bigwedge_{\ell=1}^n \Phi_\ell$$

where each Φ_{ell} is a *FOL*-Horn clause.

Theorem:(Grädel)

For Ψ a fixed *Horn* \exists *SOL* formula
 $\mathcal{M}(\mathfrak{A}, z, \phi)$ is in **P**.

We give a proof.

13

Horn formulas, IV

For simplicity let

$$\Psi = \exists X \forall x_1 \forall x_2 \dots \forall x_k \bigwedge_{\ell=1}^n \Phi_\ell$$

a τ_{graphs} -formula with X r -ary.

So each Φ_ℓ consists of atomic or negated atomic formulas $x_i \approx x_j$, $E(x_i, x_j)$ or $X(x_{i_1}, \dots, x_{i_r})$.

Let \mathfrak{A} be a structure with elements a_1, \dots, a_n .

There are n_k many assignments for the variables x_i .

Let h be the length of $\Phi = \bigwedge_{\ell} \Phi_\ell$.

14

CS 236 331:2001

Lecture 6

Horn formulas, V

We now form the formula

$$\bigwedge_z \text{subst}(\Phi, z)$$

This formula has exactly $h \cdot n^k$ many literals.

In \mathfrak{A} each atomic formula $E(a_i, a_j)$ or $a_i \approx a_j$ is true or false, so we can replace them by **true** or **false** respectively.

We replace each $X(a_{i_1}, \dots, a_{i_r})$ by a propositional variable $p_{a_{i_1}, \dots, a_{i_r}}$.

We obtain so a propositional formula $\bar{\Psi}$.

15

CS 236 331:2001

Lecture 6

Horn formulas, VI

Claim 1:

If $\mathfrak{A} \models \Psi$ then $\bar{\Psi}$ is satisfiable.

Proof: Assume $\mathfrak{A} \models \Psi$.

Then there is $U \subset A^r$ such that

$$\mathfrak{A}, U \models \forall x_1 \forall x_2 \dots \forall x_k \bigwedge_{\ell=1}^n \Phi_\ell$$

We now define an assignment

$$z(p_{\bar{a}}) = \begin{cases} 1 & \text{if } \bar{a} \in U \\ 0 & \text{if } \bar{a} \notin U \end{cases}$$

Exercise: Show that this z makes $\bar{\Psi}$ true.

16

Claim 2:

If $\bar{\Psi}$ is satisfiable then $\mathfrak{A} \models \Psi$.

Proof: Assume z is an assignment which makes $\bar{\Psi}$ true.

We define an interpretation U for X by

$$\bar{a} \in U \text{ iff } z(p_{\bar{a}}) = 1$$

Exercise: Show that

$$\mathfrak{A}, U \models \forall x_1 \forall x_2 \dots \forall x_k \bigwedge_{\ell=1}^n \Phi_{\ell}$$

17

Proof of Theorem:

- The construction of $\bar{\Psi}$ from Ψ is done in polynomial time
- The size of $\bar{\Psi}$ is polynomial in the size of Ψ .
- Using the polynomial time algorithm for *HORN SAT*, we check the satisfiability of $\bar{\Psi}$.
- Using the lemma, this settles $\mathfrak{A} \models \Psi$.

18

2SAT

Let Σ be a set of propositional clauses of at most two literals each.

These are sometimes called Krom clauses.

Both Horn and Krom are names of Logicians

2SAT is the problem of deciding whether such a Σ is satisfiable.

NL denotes the class of problems decidable in non-deterministic logarithmic space.

Theorem: *2SAT* is decidable in **NL**.

Krom \exists *SOL* is like *Horn* \exists *SOL* but with clauses of size 2 rather than Horn clauses.

It is now easy to prove that

Theorem: For fixed $\Psi \in \text{Krom}\exists\text{SOL}$ the problem $\mathcal{M}(\mathfrak{A}, z\Psi)$ is in **NL**.

The proof is exactly like for *Horn* \exists *SOL*.

19

Definability and Complexity, I

Let K be a class of finite τ -structures.

Let $\mathcal{L}(\tau) \subseteq \text{SOL}(\tau)$.

Typically $\mathcal{L}(\tau)$ is one of *Krom* \exists *SOL*(τ), *Horn* \exists *SOL*(τ), *\exists SOL*(τ), *SOL*(τ), *MSOL*(τ),

K is **definable** in $\mathcal{L}(\tau)$ if there exists $\Psi \in \mathcal{L}(\tau)$ such that

$$\mathfrak{A} \in K \text{ iff } \mathfrak{A} \models \Psi$$

Let \mathbf{C} be a complexity class.

typically *LOGSPACE*, **NL**, **P**, **NP**, **PH**, *PSPACE*

K is in \mathbf{C} iff the problem $\mathfrak{A} \in K$ can be decided with the resources allowed in \mathbf{C} .

20

We have shown:

- If K is definable in FOL then $K \in LOGSPACE$.
- If K is definable in $Krom\exists SOL$ then $K \in NL$.
- If K is definable in $Horn\exists SOL$ then $K \in P$.
- If K is definable in $\exists SOL$ then $K \in NP$.
- If K is definable in SOL then $K \in PH$.

21

We will show in the sequel for **ordered structures**

- (Grädel) If $K \in NL$, then K is definable in $Krom\exists SOL$.
- (Grädel) If $K \in P$, then K is definable in $Horn\exists SOL$.

For **arbitrary structures** we have

- (Fagin, Christen) If $K \in NP$, then K is definable in $\exists SOL$.
- (Meyer and Stockmeyer) If $K \in PH$, then K is definable in SOL .

22

LOGSPACE

What about FOL -definability and $LOGSPACE$?

Exercise:

Show that the set of words of even size is not FOL -definable.

Exercise:

Show that the set of words of even size is in $LOGSPACE$.

Exercise:

Conclude that FOL -definability is weaker than decidability in $LOGSPACE$.

Questions:

Which logic corresponds to $LOGSPACE$?

$FOL +$ deterministic transitive closure

Which complexity class corresponds to FOL ?

The circuit complexity class AC_0 .

23